

CONSOLE

2,5 kW

3,5 kW

5,0 kW



MODEL		Indoor	AF25S2SD1FA(D)	AF35S2SD1FA(D)	AF50S2SD1FA(D)
Performance data					
Output power - COOLING	nom (min-max)	kW	2,50	3,40	5,0
Output power - HEATING	nom (min-max)	kW	3,00	3,50	5,4
Power Supply		Ph/V/Hz	1/220~240/50/60	1/220~240/50/60	1/220~240/50/60
Treated air volume	(H/M/L/Q)	m3/h	450/400/350/300/250	500/450/400/350/300	600/550/500/450/400
Indoor Unit					
High sound power		dB	52	55	61
Sound pressure		dB(A)	40/32/25/20	42/34/26/21	50/42/37/32
Net dimensions	WxDxH	mm	700x210x600	700x210x600	700x210x600
Packaging dimensions	WxDxH	mm	783x303x695	783x303x695	783x303x695
Net/gross weight		kg	16,5/18,5	16,5/18,5	16,5/18,5
Installation data					
Liquid pipe	Ø	mm (inch)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Gas pipe	Ø	mm (inch)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)
Controller					
Standard			YR-HQS01	YR-HQS01	YR-HQS01