

Haier

SERENE^{NEW}

2,5 kW

3,5 kW

5,0 kW

7,1 kW



MODEL	Indoor		AS25SBBHRA-MW	AS35SBBHRA-MW	AS50SDBHRA-MW	AS71SEPHRA-MW
			AS25SBBHRA-MB	AS35SBBHRA-MB	AS50SDBHRA-MB	AS71SEPHRA-MB
Performance data						
Output power - COOLING	nom (min-max)	kW	2,6(0,8-3,4)	3,2(0,8-3,8)	5,30(2,0-6,3)	7,10(2,1-8,0)
Output power - HEATING	nom (min-max)	kW	3,0(0,7-3,7)	3,4(0,7-4,0)	5,9(1,35-6,8)	7,4(1,5-8,5)
Power Supply		Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Interconnection cable			4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0
Treated air volume	H	m3/h	610	630	800	1060
Indoor Unit						
High sound power - COOLING		dB	58	60	60	65
High sound power - HEATING		dB	58	60	60	65
Sound pressure - COOLING		dB(A)	38/33/27/19	39/34/28/20	44/40/36/31	48/42/35/27
Sound pressure - HEATING		dB(A)	38/33/27/19	39/34/28/20	44/40/36/31	48/42/35/27
Net dimensions	WxDxH	mm	810x296x200	810x296x200	983x220x321	1119x246x349
Packaging dimensions	WxDxH	mm	876x365x272	876x365x272	1050x397x301	1185x428x331
Net/gross weight		kg	8,8/11,1	8,8/11,1	11,6/14,4	15,4/18,9
Installation data						
Liquid pipe	Ø	mm (inch)	6,35	6,35	6,35	6,35
Gas pipe	Ø	mm (inch)	9,52	9,52	12,7	15,88
Controller						
Standard			HJ1-W/B	HJ1-W/B	HJ1-W/B	HJ1-W/B